

Features & Benefits

Universal ac input voltage(120-277VAC)

Compact design

94% high efficiency , low temperature rise

IP20 rated case with silicone-based potting

All-round protection: SCP, OVP, OPP

UL Class2 output, Class P

Operating temperature: -35°C~+50°C

Comply with IEEE1789, UL8750

Model List

Model Name	Rated Input Voltage	Max Output Power(Total)	Output Current(Total)	Rated Output Voltage	Efficiency	Dimension
CVP-A1-096S024U-ND	120-277VAC	96W max.	0-4000mA	24VDC	94%	150*28.5*20.7 mm/ 5.9*1.1*0.8 in.
CVP-A1-096S036U-ND	120-277VAC	96W max.	0-2667mA	36VDC	94%	150*28.5*20.7 mm/ 5.9*1.1*0.8 in.
CVP-A1-096S048U-ND	120-277VAC	96W max.	0-2000mA	48VDC	94%	150*28.5*20.7 mm/ 5.9*1.1*0.8 in.

Approvals



CLASS P


Model name code

CVP-A1	-	096	S	024	U	-	ND
①		②	③	④	⑤		⑥

①	Series	Constant Voltage Series
②	Output power	Maximum output power: 96W
③	Output Channel	Single channel
④	Output Voltage(max)	output voltage: 24V
⑤	Input voltage	120-277VAC
⑥	Dimming Control	Non-dimming



Specification:

Parameters	Symbols	Test Conditions / Comment							Min	Typ	Max	Units	
INPUT													
Input Voltage	V _{IN}								108		305	V _{AC}	
Rated Input Voltage	V _{IN RATED}								120		277	V _{AC}	
Input Frequency	f _{line}								47	50/60	63	Hz	
Input Current	I _{IN}	Full Load, V _{IN} = 120V _{AC}									1.05	A	
Inrush Current	I _{INRUSH}	Cold Start, V _{IN} = 277V _{AC}									70	A	
Leakage Current	I _{Leakage}	V _{IN} = 277V _{AC} , 60Hz									0.75	mA	
Number of Drivers per MCB(Circuit Breaker)	MCB type	B10	C10	D10	B13	C13	D13	B16	C16	D16	B20	C20	D20
	120V _{AC}	6	7	8	8	10	11	10	12	14	13	15	17
	277V _{AC}	3	6	12	4	8	16	5	9	19	7	12	24



General Characteristics

Power Factor	PF	20-100% load, $V_{IN} = 120V_{AC}$	0.9			PF
		60~100% load, $V_{IN} = 277V_{AC}$	0.9			
Total Harmonic Distortion	THD	20-100% load, $V_{IN} = 120V_{AC}$			20	%
		60~100% load, $V_{IN} = 277V_{AC}$			20	
Efficiency	η_{24V}	CVP-A1-096S024U-ND, Full load, $V_{IN} = 120V_{AC}$, Steady state	90	92		%
		CVP-A1-096S024U-ND, Full load, $V_{IN} = 277V_{AC}$, Steady state	92	94		
	η_{36V}	CVP-A1-096S036U-ND, Full load, $V_{IN} = 120V_{AC}$, Steady state	90	92		
		CVP-A1-096S036U-ND, Full load, $V_{IN} = 277V_{AC}$, Steady state	92	94		
	η_{48V}	CVP-A1-096S048U-ND, Full load, $V_{IN} = 120V_{AC}$, Steady state	90	92		
		CVP-A1-096S048U-ND, Full load, $V_{IN} = 277V_{AC}$, Steady state	92	94		
Turn On Delay Time	$T_{on, delay}$	Cold Start			0.5	S



OUTPUT

Output Voltage Tolerance	t_{OUT}				5	%
No Load Output Voltage Tolerance	$t_{NO\ LOAD}$	No Load,			3	%
Output Current	I_{OUT}	CVP-A1-096S024U-ND	0		4000	mA
		CVP-A1-096S036U-ND	0		2667	mA
		CVP-A1-096S048U-ND	0		2000	mA
Output Power	P_{OUT}				96	W
Line Regulation	$V_{OUT-LINE}$				1	%
Ripple Voltage	$V_{OUT-LINE}$	Full Load, (pk-to-pk)/Average, Without Dimmer			10	%
Output Voltage Overshoot	$V_{OVERSHOOT}$	Turning Power ON			10	%

24V Efficiency Curve TBD

36V Efficiency Curve TBD

48V Efficiency Curve TBD

Protection


Over Voltage Protection	V_{OVP}	CVP-A1-096S024U-ND, Latch mode.	28		36	V
		CVP-A1-096S036U-ND, Latch mode.	38		44	V
		CVP-A1-096S048U-ND, Latch mode.	50		60	V
Over Current Protection	I_{OCP}	CVP-A1-096S024U-ND, Hiccup mode.	4000		4500	mA
		CVP-A1-096S036U-ND, Hiccup mode.	2667		3000	mA
		CVP-A1-096S048U-ND, Hiccup mode.	2000		2300	mA
Over Power Protection	CC/CV mode.					
Short Circuit Protection	The unit can recover automatically after fault conditions is removed.					

Environment

Storage Temperature	T_{Storage}	Humidity: 5% RH to 95% RH	-40	-	+85	°C
Ambient Operating Temperature	T_a		-35	-	+50	°C
Max. Case Temperature	T_c	Hot spot on case			90	°C
Operating Relative Humidity	H_a	Non-Condensing	10		90	%
Acoustic Noise		Measured from 1m away			24	dBA
Cooling	Convection Cooling					
IP Rating	IP20					

Others

Life Time	T_{Life}	Full Load, 80°C case temperature,	50			kHrs
MTBF	T_{MTBF}	Full Load, 25°C ambient temperature	200			kHrs
Net Weight	W_{NET}			TBD		g
Warranty	5 Years Warranty at $T_c \leq 80^\circ\text{C}$					
Flicker	IEEE 1789, Title 24					



Safety Compliance

CUL/UL	UL8750, CAN/CSA-C22.2 No. 250.13
--------	----------------------------------

Electromagnetic Compliance

EMC Requirements	Standard	Conditions
EMI Emissions	FCC Title 47 Part 15B	Class B at 120VAC, Class A at 277VAC
Voltage Fluctuations and Flicker	IEC61000-3-3	
Immunity Compliance	IEC 61000-4-2	±8kV air Discharge, ±6kV Contact Discharge
	ANSI/IEEE C62.41.2	2 kV combination wave
	ANSI/IEEE C62.41.1-2002	2.5kV Ring Wave, test at 30Ω 7 Strikes/1 minute interval, Common and Differential mode, 56 total strikes
	IEC 61000-4-11	>95% dip, .5 period; 30% dip, 25 periods; 95% reduction, 250 periods
	IEC 61000-4-4	± 2kV Direct couple to Line input, 5kHz repetition rate, 15mS duration, 300mS period. 7 coupling paths, 1 minute per path (14 total combinations)

Note:

- 1. Unless otherwise specified, all the above parameters are measured at ambient temperature of 25°C and rated voltage.
- 2. Case must be grounded when installation

Packaging

Driver quantity (pcs)	Layer	Weight (kg)	Outer dimensions of Carton L*W*H(mm)
TBD	5	15.0	TBD

Mechanical Drawing:

