


Features & Benefits

- Universal ac input voltage(120-277VAC)
- Linear form factor, metal sheet case(white), side feed
- Dimmable built-in constant current independent dual outputs LED driver, dim down to true 1%.
- Standard-compliant (DiiA) digital interface including:
 - Integrated DALI bus power supply (IEC62386-250)
 - Memory Bank 1 extension, Energy Monitoring and Diagnostics (IEC62386, Parts 251, 252, 253)
 - DALI-2 Device Type 6: IEC62386-101{ed2.0}-2014, IEC62386-102{ed2.0}-2014, IEC62386-207{ed2.0}-2018
 - DALI-2 Device Type 8: IEC62386-209{ed1.0}-201
- Max. output power 30W shared between the two channels
- Low standby power: <1.2W@120VAC
- Flicker free, excellent camera compatibility, spec-grade smoothness
- UL Class2, Class P
- Comply with IEEE1789, UL8750

USB Programmable:

- ◆ Output current
- ◆ Colour temperature range
- ◆ OTP point, LED thermal protection(NTC)
- ◆ Over load protection point
- ◆ Dimming curve: log/linear
- ◆ Selectable for dimming mode: solo dimming,warm dimming,tunable white,dual dimming,DT8 dimming.
- ◆ LED Lumen Information



Model List

Model Name	Rated Input Voltage	Max Output Power(Total)	Output Current(Total)	Rated Output Voltage	Efficiency	Dimension
PDL-D1-030D1050U-DALI-PC	120-277VAC	30W max.	2*(300-1050)mA (1mA step)	2*(8-55)VDC	88%	280*30*21.5 mm 11*1.2*0.8 in.

Approvals



Model name code

<u>PDL-D1</u>	-	<u>030D</u>	<u>1050</u>	<u>U</u>	-	<u>DALI</u>	-	<u>PC</u>
①		②	③	④		⑤		⑥

①	Series	PDL Series (DALI DT8+D4i)
②	Output power	Maximum output power: 30W
③	Output Current(max)	Output current:1050mA
④	Input voltage	120-277VAC
⑤	Dimming Control	DALI-2
⑥	Programmable	USB-PC

Specification:

Parameters	Symbols	Test Conditions / Comment	Min	Typ	Max	Units
------------	---------	---------------------------	-----	-----	-----	-------

INPUT


Input Voltage	V_{IN}		108		305	V_{AC}
Rated Input Voltage	$V_{IN\ RATED}$		120		277	V_{AC}
Input Frequency	f_{line}		47	50/60	63	Hz
Input Current	I_{IN}	Full Load, $V_{IN} = 120V_{AC}$			0.35	A
Inrush Current	I_{INRUSH}	Cold Start, $V_{IN} = 277V_{AC}$			60	A
Leakage Current	$I_{Leakage}$	$V_{IN} = 277V_{AC}$ 60Hz			0.75	mA
Number of Drivers per MCB(Circuit Breaker)	MCB type	B10 C10 D10 B13 C13 D13 B16 C16 D16 B20 C20 D20				
	120V _{AC}	19 22 26 25 29 34 31 36 41 39 45 52				
	277V _{AC}	13 22 44 17 29 58 21 35 71 26 44 89				





Input Voltage	Inrush Current	t(us)10%-10%
120VAC	12.2A	186
277VAC	31.2A	180
347VAC	NA	NA

General Characteristics


Power Factor	PF	20-100% load, $V_{IN} = 120V_{AC}$	0.9		PF
		40-100% load, $V_{IN} = 277V_{AC}$	0.9		
Total Harmonic Distortion	THD	20-100% load, $V_{IN} = 120V_{AC}$		20	%
		40-100% load, $V_{IN} = 277V_{AC}$		20	
Efficiency	η	Full load, $V_{IN}=120V_{AC}$, $I_{OUT}=545mA$, $V_{OUT}=55V$, Steady state	87	88	%
		Full load, $V_{IN}=277V_{AC}$, $I_{OUT}=545mA$, $V_{OUT}=55V$, Steady state	87	88	
Turn On Delay Time	T_{on_delay}	Cold Start, 300-1050mA			0.75 S





OUTPUT

Programmable Current	Output	I_{OUT}	One Channel	300		1050	mA
Number of Output		N	Independent		2		
Output current tolerance		t	$I_{OUT}=300-1050mA$			5	%
Output Current Range		I_{OUT}	Amplitude Control.	3		1050	mA
Output Voltage		V_{OUT}		8		55	V
Output Power		P_{OUT}	See "Operating window"			30	W
Line Regulation		$V_{OUT-LINE}$				1	%
Load Regulation		$I_{OUT-LOAD}$	V_{OUT} from MIN. to MAX.			5	%
Ripple Current		$I_{OUT-RIPPLE}$	Full Load, $(I_{omax}-I_{omin})/(I_{omax}+I_{omin})$			10	%
Output Current Overshoot		$I_{OVERSHOOT}$	Turning Power ON			10	%



Programming (Optional)

The driver can be programmed through USB.

- Output current
- Colour temperature range
- OTP point, LED thermal protection(NTC)
- Over load protection point
- Dimming Curve: Logarithmic /linear
- Selectable for dimming mode: Solo Dimming, Warm Dimming, Tunable White, Dual Dimming, DT8 Dimming.
- LED Lumen Information


USB port	Programming software	"LUMIGEAR Programming Tool"
----------	----------------------	-----------------------------

	Programming tool	"Lumigear tool box"				
	Operating voltage			3.3	3.6	V
	+5V Aux power				10	mA
Programming Interface	PGT-USB-TPAC-A					
Programming Cables	PGT-USB-P254					

DALI (L Style)

It complies with the IEC62386-101:2018 Ed2.0, IEC62386-102:2018 Ed2.0, and IEC62386-207 Ed1.0 standard protocols, and can control the driver's on, off, dimming, scene, group, addressing and other functions through standard DALI instructions.

It can be controlled by a DALI Master to perform functions such as turning on/off, dimming, adjusting color temperature, scene selection, grouping, address settings, and more.




LED Thermal Protection (NTC) Characteristic

The LED thermal protection feature of the driver helps reduce the temperature of the LED module by reducing dual output current together in case of abnormal temperature conditions.

In the end application, care must be taken to place the NTC thermistor close to the hottest spot on the LED module.

If LED thermal protection is not required the NTC port on the LED power supply connector can be left open.

Graphs for reference. The derating limits can be programmed using the Light Touch.



Protection

Over Voltage Protection	V_{OVP}	Recover automatically after fault conditions is removed.			60	V
Over load Protection	P_{OLP}	Programmable. The output current will decrease when output power reach P_{OLP}	12		30	W


OLP tolerance	t_{OLP}		100		110	%
Over Temp. Protection	T_{OTP}	Programmable. Current foldback at hotspot greater than T_{OTP}		90		°C
Short Circuit Protection	Recover automatically after fault conditions is removed.					

Environment

Storage Temperature	$T_{Storage}$	Humidity: 5% RH to 95% RH	-40	-	+85	°C
Ambient Operating Temperature	T_a		-30	-	+50	°C
Max. Case Temperature	T_c	Hot spot on case			90	°C
Operating Relative Humidity	H_a	Non-Condensing	10		90	%
Acoustic Noise		Measured from 1 m w/o dimmer.			24	dBA
Cooling	Convection Cooling					
IP Rating	Dry and damp UL approved					

Others

Life Time	T_{Life}	Full Load, 80°C case temperature, $V_{IN} = 120/277V_{AC}$	50			kHrs
MTBF	T_{MTBF}	Full Load, 25°C ambient temperature $V_{IN} = 120/277V_{AC}$	200			kHrs
Net Weight	W_{NET}			280		g
Warranty	5 Years Warranty at $T_c \leq 80^\circ C$					
Flicker	IEEE 1789					



Safety Compliance

CUL/UL	UL8750, CAN/CSA-C22.2 No. 250.13
--------	----------------------------------


Electromagnetic Compliance

EMC Requirements	Standard	Conditions
EMI Emissions	FCC Title 47 Part 15B	Class B at 120V _{AC} , Class A at 277V _{AC}
Voltage Fluctuations and Flicker	IEC61000-3-3	
Immunity Compliance	IEC 61000-4-2	±8kV air Discharge, ±6kV Contact Discharge
	ANSI C62.41	± 2kV Common and Differential Mode, test at 2 Ω, 5 strikes/1minute interval (40 total strikes)
	ANSI C62.41.1	2.5kV Ring Wave, test at 30 Ω 7 Strikes/1 minute interval, Common and

		Differential mode, 56 total strikes
IEC 61000-4-11		>95% dip, .5 period; 30% dip, 25 periods; 95% reduction, 250 periods
IEC 61000-4-4		± 2kV Direct couple to Line input, 5kHz repetition rate, 15mS duration, 300mS period. 7 coupling paths, 1 minute per path (14 total combinations)

Note: Unless otherwise specified, all the above parameters are measured at ambient temperature of 25°C and rated voltage.

Typical Application:



Packaging

Driver quantity (pcs)	Layer	Weight (kg)	Outer dimensions of Carton L*W*H(mm)
63	7	18	330 X 305 X 230

Mechanical Drawing:

